



CT8xx Series

Digital TMR Latch for Consumer & Industrial Applications


Product Description

The CT8xx Series of integrated magnetic latches are designed for consumer and industrial switching applications. It is based on Crocus Technology's patented Magnetic Logic Unit™ (MLU™) technology with integrated CMOS process to provide a monolithic solution for superior sensing performance.

This series of magnetic latches feature an industry leading low power consumption as low as 200 nA. They are capable of handling large air gap applications with low magnetic fields down to 0.9 mT with best in class high frequency performance. The CT8xx is offered in active-low push-pull CMOS and open drain configuration for design flexibility. The latches are available in a low profile and small form factor 4-lead LGA and 3-lead SOT-23 packages, providing cost effective and space-saving solutions for high volume manufacturing. Please contact factory for custom solutions.



SOT-23 Package



1.40 x 1.40 x 0.44 mm LGA

Features

- High sensitivity, B_{OP} as low as 0.9 mT
- Resistant to mechanical stress
- Ultra-low power consumption as low as 200 nA
- Digital CMOS push-pull and open drain options
- Low profile and small form factor packaging
- RoHS Compliant

Applications


- IoT devices
- Smartphones, tablets, and laptops
- Door or lid closure detection
- Reed switch replacement
- Motor controllers
- Proximity detection
- Power switch or open-close detection
- Tamper-proofing for utility meters
- Fluid level detection




CT8xx Series

Digital TMR Latch
for Consumer & Industrial
Applications


Figure 1: Package Pin-out with Axis of Sensitivity Diagrams




**SOT-23 Package for
CT831/2 and CT852**



SOT-23 Package for CT834DR-IS3



LGA Package for CT832



LGA Package for CT834DR-IL1

Table 1: Pin-out Information

| Pin # for SOT23 Package | Pin # for LGA Package | Pin Name | Pin Description |
|----------------------------|--------------------------|---------------------------------------|---|
| CT831/2/4, CT852 | CT832BV, CT834 | | |
| 1 | 2 | VDD | Supply Voltage |
| 2 | 3 | $\overline{\text{OUT}}$ ANA N/C | Output Signal (Active LOW) for CT831/2 and CT852. Analog Output for CT834 in SOT23 Package No Connect for CT834 in LGA Package. |
| 3 | 4 | GND | Ground |
| - | 1 | ANA (or N/C) | Analog Output for CT834. No Connect for CT832. |



CT8xx Series

Digital TMR Latch for Consumer & Industrial Applications

Table 2: Absolute Maximum Ratings

Exceeding the absolute maximum ratings may cause permanent damage. Exposure to absolute maximum rated conditions for extended periods may affect device reliability.

| Parameter | Symbol | Min | Max | Unit |
|---|--------------------|------|----------------|------|
| Supply Voltage | V_{DD} | -0.3 | 4.0 | V |
| Push-pull Output (Active LOW) | V_{OUT_PP} | -0.3 | $V_{DD} + 0.3$ | V |
| Open Drain Output Voltage (Active LOW) | V_{OUT_OD} | -0.3 | 5.5 | V |
| Analog Output | V_{ANA} | -0.3 | $V_{DD} + 0.3$ | V |
| Input and Output Current | I_{IN} / I_{OUT} | -10 | +10 | mA |
| Junction temperature | T_J | -40 | +125 | °C |
| Storage temperature | T_{STG} | -65 | +150 | °C |
| Soldering temperature | T_{SOL} | | +260 | °C |
| ESD Level, Human Body Model per JESD22-A114 | V_{ESD_HBM} | ±4.0 | | kV |

Table 3: Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for the actual device operation. Recommended operating conditions are specified to ensure optimal performance to the data sheet specifications. Crocus Technology does not recommend exceeding them or designing to absolute maximum ratings.

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|-------------------------|-----------|------------|-----|-------------------|------|------|
| Supply Voltage | V_{DD} | | 2.7 | 3.0 | 3.6 | V |
| Output Voltage | V_{OUT} | | | | 3.6 | V |
| Operating Magnetic Flux | B | | | $4 \times B_{OP}$ | | mT |
| Ambient Temperature | T_A | | -40 | +25 | +125 | °C |
| Junction Temperature | T_J | | -40 | | +125 | °C |

Table 4: Thermal Properties

Junction-to-ambient thermal resistance is a function of application and board layout and is determined in accordance to JEDEC standard JESD51 for a four (4) layer 2s2p FR-4 printed circuit board (PCB). Special attention must be paid not to exceed junction temperature $T_{J(MAX)}$ at a given ambient temperature.

| Parameter | Symbol | Min | Typ | Max | Unit |
|--|----------------------|-----|-----|-----|------|
| Junction-to-Ambient Thermal Resistance for SOT23 Package | $\theta_{JA(SOT23)}$ | | 202 | | °C/W |
| Junction-to-Ambient Thermal Resistance for LGA Package | $\theta_{JA(LGA)}$ | | 165 | | °C/W |



CT8xx Series

Digital TMR Latch for Consumer & Industrial Applications

Table 5: Electrical Characteristics for CT8xx Series

Unless otherwise specified: $V_{DD} = 2.7 \text{ V to } 3.6 \text{ V}$, $T_A = -40^\circ\text{C to } +125^\circ\text{C}$. Typical values are $V_{DD} = 3.0 \text{ V}$ and $T_A = +25^\circ\text{C}$.

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|---|------------------|---------------------------|---------------------|---------|---------------------|---------------|
| Power-On Time | t_{ON} | $V_{DD} > 2.7 \text{ V}$ | | 500 | | μs |
| Output Voltage High $\overline{\text{OUT}}$ | V_{OH} | $I_{OUT} = -2 \text{ mA}$ | $0.9 \times V_{DD}$ | | | V |
| Output Voltage Low $\overline{\text{OUT}}$ | V_{OL} | $I_{OUT} = +2 \text{ mA}$ | | | $0.1 \times V_{DD}$ | V |
| Current for $\overline{\text{OUT}}$ | I_{OUT} | | | ± 2 | | mA |
| Under-voltage Lockout Threshold, Rising V_{DD} | V_{UVLO_RISE} | Rising V_{DD} | | 2.20 | 2.60 | V |
| Under-voltage Lockout Threshold, Falling V_{DD} | V_{UVLO_FALL} | Falling V_{DD} | 1.90 | 2.15 | | V |
| Under-voltage Lockout Hysteresis | V_{UV_HYST} | | | 50 | | mV |

Typical Characteristics for CT8xx

$V_{DD} = 3.0 \text{ V}$ and $T_A = +25^\circ\text{C}$, $C_{DD} = 1.0 \mu\text{F}$ (unless otherwise specified).




Figure 2. Power-On Time for Push-pull Output (V_{DD} and OUT)




Figure 3. Power-On Time for Open Drain Output (V_{DD} and OUT)



CT8xx Series

Digital TMR Latch for Consumer & Industrial Applications

Table 6: Electrical Characteristics for CT831BV

Unless otherwise specified: $V_{DD} = 2.7\text{ V to }3.6\text{ V}$, $T_A = -40^\circ\text{C to }+125^\circ\text{C}$. Typical values are $V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$.

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|-----------------------------|---------------|-----------------------------------|------|------|------|---------------|
| Average Supply Current | $I_{DD(AVG)}$ | $t = 10\text{ s}$ | | 200 | 700 | nA |
| Output Voltage High | V_{OH} | | | | 5.5 | V |
| Output Voltage Low | V_{OL} | $I_{OUT} \leq 20\text{ mA}$ | 0 | | 0.5 | V |
| High Output Leakage Current | I_{LEAK} | $V_{OH} = 5.5\text{ V}$, $B = 0$ | | 20 | | pA |
| Sampling Frequency | f_s | | 1 | 2 | 4 | Hz |
| Active Mode Time | t_{ACT} | | | 1.4 | | μs |
| Idle Mode Time | t_{SLP} | | | 500 | | ms |
| Operate Point | B_{OPS} | | 2.7 | 3.0 | 3.8 | mT |
| Operate Point | B_{OPN} | | -3.8 | -3.0 | -2.7 | mT |
| Release point | B_{RPS} | | 1.8 | 2.0 | 2.7 | mT |
| Release point | B_{RPN} | | -2.7 | -2.0 | -1.8 | mT |
| Hysteresis | B_{HYST} | $B_{HYST} = B_{OP} - B_{RP}$ | 0.5 | 1.0 | | mT |

Table 7: Electrical Characteristics for CT832BV

Unless otherwise specified: $V_{DD} = 2.7\text{ V to }3.6\text{ V}$, $T_A = -40^\circ\text{C to }+125^\circ\text{C}$. Typical values are $V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$.

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|------------------------|---------------|------------------------------|------|------|------|---------------|
| Average Supply Current | $I_{DD(AVG)}$ | $t = 10\text{ s}$ | | 200 | 700 | nA |
| Sampling Frequency | f_s | | 1 | 2 | 4 | Hz |
| Active Mode Time | t_{ACT} | | | 1.4 | | μs |
| Idle Mode Time | t_{IDLE} | | | 500 | | ms |
| Operate Point | B_{OPS} | | 2.7 | 3.0 | 3.8 | mT |
| Operate Point | B_{OPN} | | -3.8 | -3.0 | -2.7 | mT |
| Release point | B_{RPS} | | 1.8 | 2.0 | 2.7 | mT |
| Release point | B_{RPN} | | -2.7 | -2.0 | -1.8 | mT |
| Hysteresis | B_{HYST} | $B_{HYST} = B_{OP} - B_{RP}$ | 0.5 | 1.0 | | mT |



Typical Characteristics for CT831BV and CT832BV

$V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$, $C_{DD} = 1.0\text{ }\mu\text{F}$ (unless otherwise specified).




Figure 4. Average Supply Current vs. Supply Voltage vs. Temperature




Figure 5. Average Supply Current vs. Temperature vs. Supply Voltage




Figure 6. Sampling Frequency vs. Supply Voltage vs. Temperature



Table 8: Electrical Characteristics for CT832SK

Unless otherwise specified: $V_{DD} = 2.7\text{ V to }3.6\text{ V}$, $T_A = -40^\circ\text{C to }+125^\circ\text{C}$. Typical values are $V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$.

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|------------------------|---------------|------------------------------|------|------|------|---------------|
| Average Supply Current | $I_{DD(AVG)}$ | $t = 10\text{ s}$ | | 230 | 700 | nA |
| Sampling Frequency | f_S | | 7 | 10 | 13 | Hz |
| Active Mode Time | t_{ACT} | | | 1.4 | | μs |
| Idle Mode Time | t_{IDLE} | | | 100 | | ms |
| Operate Point | B_{OPS} | | 0.8 | 0.9 | 1.2 | mT |
| Operate Point | B_{OPN} | | -1.2 | -0.9 | -0.8 | mT |
| Release point | B_{RPS} | | 0.3 | 0.5 | 0.7 | mT |
| Release point | B_{RPN} | | -0.7 | -0.5 | -0.3 | mT |
| Hysteresis | B_{HYST} | $B_{HYST} = B_{OP} - B_{RP}$ | 0.3 | 0.4 | | mT |

Table 9: Electrical Characteristics for CT832EK

Unless otherwise specified: $V_{DD} = 2.7\text{ V to }3.6\text{ V}$, $T_A = -40^\circ\text{C to }+125^\circ\text{C}$. Typical values are $V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$.

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|------------------------|---------------|------------------------------|-----|------|-----|---------------|
| Average Supply Current | $I_{DD(AVG)}$ | $t = 10\text{ s}$ | | 230 | 700 | nA |
| Sampling Frequency | f_S | | 7 | 10 | 13 | Hz |
| Active Mode Time | t_{ACT} | | | 1.4 | | μs |
| Idle Mode Time | t_{IDLE} | | | 100 | | ms |
| Operate Point | B_{OPS} | | | 7.0 | | mT |
| Operate Point | B_{OPN} | | | -7.0 | | mT |
| Release Point | B_{RPS} | | | 5.0 | | mT |
| Release Point | B_{RPN} | | | -5.0 | | mT |
| Hysteresis | B_{HYST} | $B_{HYST} = B_{OP} - B_{RP}$ | | 2.0 | | mT |



Typical Characteristics for CT832SK and CT832EK

$V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$, $C_{DD} = 1.0\text{ }\mu\text{F}$ (unless otherwise specified).




Figure 7. Average Supply Current vs. Supply Voltage vs. Temperature




Figure 8. Average Supply Current vs. Temperature vs. Supply Voltage




Figure 9. Sampling Frequency vs. Supply Voltage vs. Temperature



Table 10: Electrical Characteristics for CT832SL

Unless otherwise specified: $V_{DD} = 2.7\text{ V to }3.6\text{ V}$, $T_A = -40^\circ\text{C to }+125^\circ\text{C}$. Typical values are $V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$.

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|------------------------|---------------|------------------------------|------|------|------|---------------|
| Average Supply Current | $I_{DD(AVG)}$ | $t = 10\text{ s}$ | | 1.4 | 2.5 | μA |
| Sampling Frequency | f_S | | 165 | 250 | 300 | Hz |
| Active Mode Time | t_{ACT} | | | 1.4 | | μs |
| Idle Mode Time | t_{IDLE} | | | 4.0 | | ms |
| Operate Point | B_{OPS} | | 0.8 | 0.9 | 1.2 | mT |
| Operate Point | B_{OPN} | | -1.2 | -0.9 | -0.8 | mT |
| Release point | B_{RPS} | | 0.3 | 0.5 | 0.7 | mT |
| Release point | B_{RPN} | | -0.7 | -0.5 | -0.3 | mT |
| Hysteresis | B_{HYST} | $B_{HYST} = B_{OP} - B_{RP}$ | 0.3 | 0.4 | | mT |

Table 11: Electrical Characteristics for CT832BL

Unless otherwise specified: $V_{DD} = 2.7\text{ V to }3.6\text{ V}$, $T_A = -40^\circ\text{C to }+125^\circ\text{C}$. Typical values are $V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$.

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|------------------------|---------------|------------------------------|------|------|------|---------------|
| Average Supply Current | $I_{DD(AVG)}$ | $t = 10\text{ s}$ | | 1.4 | 2.5 | μA |
| Sampling Frequency | f_S | | 165 | 250 | 300 | Hz |
| Active Mode Time | t_{ACT} | | | 1.4 | | μs |
| Idle Mode Time | t_{IDLE} | | | 4.0 | | ms |
| Operate Point | B_{OPS} | | 2.7 | 3.0 | 3.8 | mT |
| Operate Point | B_{OPN} | | -3.8 | -3.0 | -2.7 | mT |
| Release point | B_{RPS} | | 1.8 | 2.0 | 2.7 | mT |
| Release point | B_{RPN} | | -2.7 | -2.0 | -1.8 | mT |
| Hysteresis | B_{HYST} | $B_{HYST} = B_{OP} - B_{RP}$ | 0.5 | 1.0 | | mT |



Typical Characteristics for CT832SL and CT832BL

$V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$, $C_{DD} = 1.0\text{ }\mu\text{F}$ (unless otherwise specified).




Figure 10. Average Supply Current vs. Supply Voltage vs. Temperature




Figure 11. Average Supply Current vs. Temperature vs. Supply Voltage




Figure 12. Sampling Frequency vs. Supply Voltage vs. Temperature



Table 12: Electrical Characteristics for CT832DM

Unless otherwise specified: $V_{DD} = 2.7\text{ V to }3.6\text{ V}$, $T_A = -40^\circ\text{C to }+125^\circ\text{C}$. Typical values are $V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$.

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|------------------------|---------------|------------------------------|------|------|------|---------------|
| Average Supply Current | $I_{DD(AVG)}$ | $t = 10\text{ s}$ | | 8 | 13 | μA |
| Sampling Frequency | f_S | | 1.63 | 2.50 | 3.25 | kHz |
| Active Mode Time | t_{ACT} | | | 1.4 | | μs |
| Idle Mode Time | t_{IDLE} | | | 400 | | μs |
| Operate Point | B_{OPS} | | 1.3 | 1.5 | 1.8 | mT |
| Operate Point | B_{OPN} | | -1.8 | -1.5 | -1.3 | mT |
| Release point | B_{RPS} | | 0.8 | 1.0 | 1.3 | mT |
| Release point | B_{RPN} | | -1.3 | -1.0 | -0.8 | mT |
| Hysteresis | B_{HYST} | $B_{HYST} = B_{OP} - B_{RP}$ | 0.3 | 0.5 | | mT |

Typical Characteristics for CT832DM

$V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$, $C_{DD} = 1.0\text{ }\mu\text{F}$ (unless otherwise specified).




Figure 13. Average Supply Current vs. Supply Voltage vs. Temperature




Figure 14. Average Supply Current vs. Temperature vs. Supply Voltage



Typical Characteristics for CT832DM

$V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$, $C_{DD} = 1.0\text{ }\mu\text{F}$ (unless otherwise specified).




Figure 15. Sampling Frequency vs. Supply Voltage vs. Temperature



Table 13: Electrical Characteristics for CT832BH

Unless otherwise specified: $V_{DD} = 2.7\text{ V to }3.6\text{ V}$, $T_A = -40^\circ\text{C to }+125^\circ\text{C}$. Typical values are $V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$.

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|------------------------|---------------|------------------------------|------|------|------|---------------|
| Average Supply Current | $I_{DD(AVG)}$ | $t = 10\text{ s}$ | | 1.6 | 2.7 | mA |
| Sampling Frequency | f_s | | 7 | 10 | 13 | kHz |
| Active Mode Time | t_{ACT} | | | 1.4 | | μs |
| Idle Mode Time | t_{IDLE} | | | 100 | | μs |
| Operate Point | B_{OPS} | | 2.7 | 3.0 | 3.8 | mT |
| Operate Point | B_{OPN} | | -3.8 | -3.0 | -2.7 | mT |
| Release Point | B_{RPS} | | 1.8 | 2.0 | 2.7 | mT |
| Release Point | B_{RPN} | | -2.7 | -2.0 | -1.8 | mT |
| Hysteresis | B_{HYST} | $B_{HYST} = B_{OP} - B_{RP}$ | 0.5 | 1.0 | | mT |

Typical Characteristics for CT832BH

$V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$, $C_{DD} = 1.0\text{ }\mu\text{F}$ (unless otherwise specified).




Figure 16. Sampling Frequency vs. Supply Voltage vs. Temperature



Table 14: Electrical Characteristics for CT834DR

Unless otherwise specified: $V_{DD} = 2.7\text{ V to }3.6\text{ V}$, $T_A = -40^\circ\text{C to }+85^\circ\text{C}$. Typical values are $V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$.

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|---------------------------------------|-------------------|--|----------------------|-----|----------------------|------------------|
| Operating Temperature | T_A | | -40 | | +85 | $^\circ\text{C}$ |
| Average Supply Current | $I_{DD(AVG)}$ | $t = 10\text{ s}$ | | 1.5 | 2.7 | mA |
| Maximum Drive Capability | $I_{DRV(MAX)}$ | V_{ANA} covers 19% V_{DD} to 81% V_{DD} span | -10 | | +10 | μA |
| Output Capacitive Load | C_L | | | | 10 | pF |
| Analog Output Magnetic Field Range | B_{ANA} | | -1.0 | | +1.0 | mT |
| Analog Output Voltage Range | V_{ANA} | | $0.19 \times V_{DD}$ | | $0.81 \times V_{DD}$ | V |
| Voltage Output Quiescent | V_{OQ} | | 45 | 50 | 55 | % V_{DD} |
| Sensitivity @ $T = +25^\circ\text{C}$ | $S_{T=25}$ | $T_A = +25^\circ\text{C}$ | 176 | 200 | 224 | mV/V/mT |
| Sensitivity @ Full Temperature Range | S_{FULL_RANGE} | $T_A = -40^\circ\text{C to }+85^\circ\text{C}$ | 140 | 200 | 260 | mV/V/mT |

Typical Characteristics for CT834DR

$V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$, $C_{DD} = 1.0\text{ }\mu\text{F}$ (unless otherwise specified).




Figure 17. Average Supply Current vs. Supply Voltage vs. Temperature




Figure 18. Average Supply Current vs. Temperature vs. Supply Voltage



CT8xx Series

Digital TMR Latch for Consumer & Industrial Applications

Table 15: Electrical Characteristics for CT852AN

Unless otherwise specified: $V_{DD} = 2.7\text{ V to }3.6\text{ V}$, $T_A = -40^\circ\text{C to }+125^\circ\text{C}$. Typical values are $V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$.

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|------------------------|---------------|-------------------|------|------|------|---------------|
| Average Supply Current | $I_{DD(AVG)}$ | $t = 10\text{ s}$ | | 1.7 | 3.3 | μA |
| Sampling Frequency | f_S | | 325 | 500 | 600 | Hz |
| Active Mode Time | t_{ACT} | | | 1.4 | | μs |
| Idle Mode Time | t_{IDLE} | | | 2.0 | | ms |
| Operate Point | B_{OPS} | | 0.8 | 1.0 | 1.4 | mT |
| Release point | B_{RPN} | | -1.4 | -1.0 | -0.8 | mT |

Typical Characteristics for CT852AN

$V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$, $C_{DD} = 1.0\text{ }\mu\text{F}$ (unless otherwise specified).




Figure 19. Average Supply Current vs. Supply Voltage vs. Temperature




Figure 20. Average Supply Current vs. Temperature vs. Supply Voltage



Typical Characteristics for CT852AN

$V_{DD} = 3.0\text{ V}$ and $T_A = +25^\circ\text{C}$, $C_{DD} = 1.0\text{ }\mu\text{F}$ (unless otherwise specified).





Figure 21. Sampling Frequency vs. Supply Voltage vs. Temperature



Figure 22: Omnipolar Magnetic Flux




Output Behavior versus Magnetic Field

| Characteristic | Conditions | Output |
|----------------|-------------------|------------|
| South Pole | $B > B_{OPS}$ | Low (ON) |
| | $0 < B < B_{RPS}$ | High (OFF) |
| North Pole | $B < B_{OPN}$ | Low (ON) |
| | $0 > B > B_{RPN}$ | High (OFF) |



Figure 23: Bipolar Magnetic Flux



Output Behavior versus Magnetic Field


| Characteristic | Conditions | Output |
|----------------|--------------|------------|
| South Pole | $B > B_{OP}$ | Low (ON) |
| North Pole | $B < B_{RP}$ | High (OFF) |




Figure 24: Application Circuits

A decoupling capacitor (C_{DD}) between the supply voltage and ground is required with placement close to the magnetic switch. A typical capacitor value of 1 μF (Ceramic) will suffice. For the open drain output, maximum V_{SYS} should not exceed 5.5 V.

CT831 Open Drain Output




CT832 & CT852 Digital Output



For the analog output, a simple RC filter is recommended on the ANA output as shown below:

CT834 Analog Output






CT8xx Series


Digital TMR Latch
for Consumer & Industrial
Applications

Figure 25: MLU Sensor Location



SOT23 Package

| Symbols | Nominal Dimensions (mm) |
|---------|-------------------------|
| A | 1.60 |
| B | 2.90 |
| C | 0.80 |
| D | 1.45 |



LGA Package

| Symbols | Nominal Dimensions (mm) |
|---------|-------------------------|
| A | 1.40 |
| B | 1.40 |
| C | 0.50 |
| D | 0.50 |



CT8xx Series

Digital TMR Latch for Consumer & Industrial Applications

Table 16: Order Guide

| Part Number | Polarity | Output Type | B _{OP} | B _{RP} | I _{DD(AVG)} | f _S | Description |
|-------------|-----------|-------------|-----------------|-----------------|----------------------|----------------|--|
| CT831BV-HS3 | Omnipolar | Open Drain | | | | | Omnipolar Magnetic Latch SOT-23 Package, Tape & Reel Packaging |
| CT831BV-IS3 | | Push-Pull | ±3.0 mT | ±2.0 mT | 200 nA | 2 Hz | Omnipolar Magnetic Latch LGA Package, Tape & Reel Packaging |
| CT832BV-HL1 | | | | | | | Omnipolar Magnetic Latch SOT-23 Package, Tape & Reel Packaging |
| CT832BV-IL1 | | | | | | | Omnipolar Magnetic Latch SOT-23 Package, Tape & Reel Packaging |
| CT832BV-HS3 | | | ±0.9 mT | ±0.5 mT | 230 nA | 10 Hz | Omnipolar Magnetic Latch SOT-23 Package, Tape & Reel Packaging |
| CT832BV-IS3 | | | | | | | Omnipolar Magnetic Latch SOT-23 Package, Tape & Reel Packaging |
| CT832SK-HS3 | | | | | | | Omnipolar Magnetic Latch SOT-23 Package, Tape & Reel Packaging |
| CT832SK-IS3 | | | ±0.9 mT | ±0.5 mT | 1.4 µA | 250 Hz | Omnipolar Magnetic Latch SOT-23 Package, Tape & Reel Packaging |
| CT832SL-HS3 | | | | | | | Omnipolar Magnetic Latch SOT-23 Package, Tape & Reel Packaging |
| CT832SL-IS3 | | | | | | | Omnipolar Magnetic Latch SOT-23 Package, Tape & Reel Packaging |
| CT832BL-HS3 | | | ±3.0 mT | ±2.0 mT | 1.4 µA | 250 Hz | Omnipolar Magnetic Latch SOT-23 Package, Tape & Reel Packaging |
| CT832BL-IS3 | | | | | | | Omnipolar Magnetic Latch SOT-23 Package, Tape & Reel Packaging |
| CT832DM-HS3 | | | ±1.5 mT | ±1.0 mT | 12 µA | 2.5 kHz | Omnipolar Magnetic Latch SOT-23 Package, Tape & Reel Packaging |
| CT832DM-IS3 | | | | | | | Omnipolar Magnetic Latch SOT-23 Package, Tape & Reel Packaging |
| CT832BH-HL1 | | | ±3.0 mT | ±2.0 mT | 1.6 mA | 10 kHz | Omnipolar Magnetic Latch LGA Package, Tape & Reel Packaging |
| CT832BH-IL1 | | | | | | | Omnipolar Magnetic Latch LGA Package, Tape & Reel Packaging |
| CT832EK-HS3 | | | ±7.0 mT | ±5.0 mT | 230 nA | 10 Hz | Omnipolar Magnetic Latch SOT-23 Packages, Tape & Reel Packaging |
| CT832EK-IS3 | | | | | | | Omnipolar Magnetic Latch SOT-23 Packages, Tape & Reel Packaging |
| CT834DR-IL1 | | Analog | N/A | N/A | 1.5 mA | Continuous | Omnipolar Magnetic Latch LGA Packages, Tape & Reel Packaging |
| CT834DR-IS3 | | | | | | | Omnipolar Magnetic Latch SOT-23 Packages, Tape & Reel Packaging |
| CT852AN-HS3 | Bipolar | Push-Pull | +1.0 mT | -1.0 mT | 2.6 µA | 500 Hz | Bipolar Magnetic Latch SOT-23 Package, Tape & Reel Packaging |
| CT852AN-IS3 | | | | | | | Bipolar Magnetic Latch SOT-23 Package, Tape & Reel Packaging |



CT8xx Series

Digital TMR Latch for Consumer & Industrial Applications

Table 17. Packaging Information

| Orderable Part Number | Package Type | Pins | Package Quantity | Lead Finish | Eco Plan ⁽¹⁾ | MSL Rating ⁽²⁾ | Operating Temperature | Device Marking ⁽³⁾ |
|-----------------------|--------------|------|------------------|-------------|-------------------------|---------------------------|-----------------------|-------------------------------|
| CT831BV-HS3 | SOT-23 | 3 | 3,000 | Sn | Green & RoHS | 1 | -40°C to +125°C | JA YWWS |
| CT831BV-IS3 | SOT-23 | 3 | 3,000 | Sn | Green & RoHS | 1 | -40°C to +85°C | JA YWWS |
| CT832BV-HL1 | LGA | 4 | 3,000 | Au | Green & RoHS | 3 | -40°C to +125°C | A YZ |
| CT832BV-IL1 | LGA | 4 | 3,000 | Au | Green & RoHS | 3 | -40°C to +85°C | A YZ |
| CT832BV-HS3 | SOT-23 | 3 | 3,000 | Sn | Green & RoHS | 1 | -40°C to +125°C | HA YWWS |
| CT832BV-IS3 | SOT-23 | 3 | 3,000 | Sn | Green & RoHS | 1 | -40°C to +85°C | HA YWWS |
| CT832SK-HS3 | SOT-23 | 3 | 3,000 | Sn | Green & RoHS | 1 | -40°C to +125°C | HC YWWS |
| CT832SK-IS3 | SOT-23 | 3 | 3,000 | Sn | Green & RoHS | 1 | -40°C to +85°C | HC YWWS |
| CT832SL-HS3 | SOT-23 | 3 | 3,000 | Sn | Green & RoHS | 1 | -40°C to +125°C | HE YWWS |
| CT832SL-IS3 | SOT-23 | 3 | 3,000 | Sn | Green & RoHS | 1 | -40°C to +85°C | HE YWWS |
| CT832BL-HS3 | SOT-23 | 3 | 3,000 | Sn | Green & RoHS | 1 | -40°C to +125°C | HB YWWS |
| CT832BL-IS3 | SOT-23 | 3 | 3,000 | Sn | Green & RoHS | 1 | -40°C to +85°C | HB YWWS |
| CT832DM-HS3 | SOT-23 | 3 | 3,000 | Sn | Green & RoHS | 1 | -40°C to +125°C | HD YWWS |
| CT832DM-IS3 | SOT-23 | 3 | 3,000 | Sn | Green & RoHS | 1 | -40°C to +85°C | HD YWWS |
| CT832BH-HL1 | LGA | 4 | 3,000 | Au | Green & RoHS | 3 | -40°C to +125°C | E YZ |
| CT832BH-IL1 | LGA | 4 | 3,000 | Au | Green & RoHS | 3 | -40°C to +85°C | E YZ |
| CT832EK-HS3 | SOT-23 | 3 | 3,000 | Sn | Green & RoHS | 1 | -40°C to +125°C | HF YWWS |
| CT832EK-IS3 | SOT-23 | 3 | 3,000 | Sn | Green & RoHS | 1 | -40°C to +85°C | HF YWWS |
| CT834DR-IL1 | LGA | 4 | 3,000 | Au | Green & RoHS | 3 | -40°C to +85°C | D YZ |
| CT834DR-IS3 | SOT-23 | 3 | 3,000 | Sn | Green & RoHS | 1 | -40°C to +85°C | HT YWWS |
| CT852AN-HS3 | SOT-23 | 3 | 3,000 | Sn | Green & RoHS | 1 | -40°C to +125°C | HS YWWS |
| CT852AN-IS3 | SOT-23 | 3 | 3,000 | Sn | Green & RoHS | 1 | -40°C to +85°C | HS YWWS |

(1) RoHS is defined as semiconductor products that are compliant to the current EU RoHS requirements. It also will meet the requirement that RoHS substances do not exceed 0.1% by weight in homogeneous materials. Green is defined as the content of Chlorine (Cl), Bromine (Br) and Antimony Trioxide based flame retardants satisfy JS709B low halogen requirements of $\leq 1,000$ ppm.

(2) MSL Rating = Moisture Sensitivity Level Rating as defined by JEDEC industry standard classifications.


(3) Device Marking for SOT23 is defined as XZ YWWS where XZ = part number, Y = year, WW = work week and S = sequential number. LGA is defined as X where X = part number and YZ = date code information.



CT8xx Series

Digital TMR Latch
for Consumer & Industrial
Applications

Figure 26: 3-Lead SOT-23 Package Dimensions




| SYMBOLS | DIMENSIONS IN MILLIMETERS | | |
|---------|---------------------------|------|------|
| | MIN | NOM | MAX |
| A | 1.05 | 1.20 | 1.35 |
| A1 | 0.00 | 0.10 | 0.15 |
| A2 | 1.00 | 1.10 | 1.20 |
| b | 0.30 | — | 0.50 |
| b1 | 0.30 | 0.35 | 0.45 |
| c | 0.08 | — | 0.22 |
| c1 | 0.08 | 0.13 | 0.20 |
| D | 2.80 | 2.90 | 3.00 |
| E | 2.60 | 2.80 | 3.00 |
| E1 | 1.50 | 1.60 | 1.70 |
| e | 0.95 BSC | | |
| e1 | 1.90 BSC | | |
| L | 0.35 | 0.43 | 0.60 |
| L1 | 0.60 REF | | |
| L2 | 0.25 BSC. | | |
| R | 0.10 | — | — |
| R1 | 0.10 | — | 0.25 |
| θ | 0° | 4° | 8° |
| θ1 | 5° | 6° | 15° |
| θ2 | 5° | 8° | 15° |



CT8xx Series

Digital TMR Latch
for Consumer & Industrial
Applications

Figure 27: 4-Lead LGA Package Dimensions



NOTE: ALL DIMENSIONS ARE IN MILLIMETERS.

| SYMBOLS | DIMENSIONS IN MILLIMETERS | | |
|---------|---------------------------|------------|-------|
| | MIN. | NOM. | MAX. |
| A | 0.386 | 0.436 | 0.486 |
| b | 0.30 | 0.35 | 0.40 |
| c | --- | 0.136 REF. | --- |
| D | 1.35 | 1.40 | 1.45 |
| E | 1.35 | 1.40 | 1.45 |
| e | --- | 0.65 | --- |
| L | 0.50 | 0.55 | 0.60 |
| L1 | 0.15 | 0.20 | 0.25 |
| L3 | 0.30 | 0.35 | 0.40 |
| s | 0.15 | 0.20 | 0.25 |



CROCUS TECHNOLOGY
Intelligence in Sensing™

CT8xx Series

Digital TMR Latch for Consumer & Industrial Applications

Disclaimer: The contents of this document are provided for informational purposes only. CROCUS TECHNOLOGY, INC. AND CROCUS TECHNOLOGY SA (COLLECTIVELY "CROCUS") MAKE NO REPRESENTATIONS OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH RESPECT TO THE ACCURACY OR COMPLETENESS OF THE CONTENTS HEREIN, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Crocus reserves the right to make changes to the specifications and product descriptions, and/or to discontinue or make changes to its products at any time without notice. Crocus's products have not been designed, tested, or manufactured for use and should not be used in applications where the failure, malfunction or inaccuracy of the Products carries a risk of death or serious bodily injury or damage to tangible property, including, but not limited to, life support systems, nuclear facilities, military, aircraft navigation or communication, emergency systems, harsh environments, or other applications with a similar degree of potential hazard.

© 2017 Crocus Technology, Inc. and Crocus Technology SA. All rights reserved. Crocus Technology, Intelligence in Sensing, MLU, and combinations thereof are trademarks of Crocus Technology, Inc. and Crocus Technology SA.